

# EIB603TYCRF - Heat Alarm + RadioLINK

## 10-Year Lithium Battery~ Hard-wire Interconnection

### Key Features

- ▶ Practically eliminates nuisance alarms
- ▶ Suitable for kitchens and areas where smoke alarms may be subjected to nuisance alarms
- ▶ Aesthetically pleasing, compact design
- ▶ Battery capacity is sufficient to outlast the useful lifespan of the alarm
- ▶ Large, easy to use TEST button
- ▶ Interconnect up to 12 battery powered alarms
- ▶ Easy to fit twist-on base
- ▶ RadioLINK interconnectivity - one alarm sounds all alarms in system
- ▶ 5 Year Guarantee (limited)

### Product Description

The EIB603TYCRF alarm is activated by heat from a fire, not smoke, which makes it ideal for kitchen installations where smoke detectors are prone to nuisance alarms.

The EIB603TYCRF has a 10-year lithium battery that is non replaceable.

Heat Alarms are supplementary to Smoke Alarms and must always be interconnected to other smoke alarms in the dwelling or escape routes to ensure that all occupants are alerted to the danger.

RadioLINK wireless interconnection technology is built-in to interconnect this alarm with the rest of the system. This will automatically activate once the alarm is powered up.

Up to 12 battery powered smoke and heat alarms may be linked using hardwire or RF connectivity.

RadioLINK enabled smoke and/or heat alarms can be house coded as a system to prevent communication with other nearby RadioLINK systems.



### Technical Specification

<b>Sensor Type:</b>	Thermistor - activates at 58°C
<b>Battery:</b>	9V 10-year Lithium Battery (non replaceable)
<b>Button Test:</b>	Pressing the test button tests the sensor, electronics and horn
<b>Power-on Indicator:</b>	Red LED flashes through cover every 40 seconds
<b>Alarm Indicator:</b>	Red LED flashes rapidly on the alarm sensing the fire and the sounder is activated. The sounders on all interconnected alarms are also activated
<b>Temperature:</b>	Operating - 0°C to 40°C <sup>1</sup>
<b>Humidity Range:</b>	15% to 95% Relative Humidity (non condensing)
<b>Hardwire Interconnect:</b>	Interconnect up to 12 alarms and remote control devices
<b>RadioLINK Interconnect:</b>	Interconnect for up to 12 battery powered RadioLINK alarms and remote control devices
<b>Fixing:</b>	Screw fixings supplied
<b>Dimensions:</b>	115mm x 55mm
<b>Weight:</b>	200g
<b>Warranty:</b>	5 year (limited) warranty
<b>Approvals:</b>	Conforms to AS1603.3:1996 Manufactured to ISO 9001:2000 quality standards



1. Temperature and Humidity conditions are for normal operation and storage. Units will function outside these ranges as required by the specific product Standards. Extended exposure to conditions outside these ranges can reduce product life. For advice on prolonged operation outside these ranges consult the manufacturer.

Due to continual product development, Brooks reserve the right to alter product details and specifications without prior notice.

**Head Office:** Sydney, 4 Pike Street, Rydalmere 2116 | PO Box 7050 Silverwater BC1811  
**Regional Offices:** Melbourne - Brisbane - Adelaide - Perth - Auckland  
 www.brooks.com.au - Toll Free 1300 783 473