

BVADW Visual Alarm Device Wall Mount

BVADWR	Ceiling Mount Visual Alarm Device Red – 7.5m coverage
BVADWW	Ceiling Mount Visual Alarm Device White – 7.5m coverage



The Visual Alarm Device Wall Mount BVADW is suitable for a variety of applications available in a red or white body and compatible with the full range of 6 bases.

A patented lens design distributes light to achieve the required illumination specified by AS7240.23, whilst using minimum current consumption.

Features

- Ultra low current consumption of 10mA
- Up to 7.5m room coverage
- 0.5Hz or 1Hz flash rate
- Coverage switch to 2.5m

Benefits

- Use where current consumption is a key consideration
- Ideal for bedrooms, bathrooms and toilets
- Switch flash rate to 0.5Hz to reduce current consumption
- Reduces power consumption by up to 50%

Technical Specification

Mounting Type	Wall
Voltage	9 – 60VDC
Current	10 – 25mA dependent on setting
Coverage (y)	7.5m (Switchable to 2.5m)*
Mounting Height (x)	2.4m (max)
Coverage Volume Code	W-2.4 - 7.5
Coverage Volume	135m ³ (15m ³)
Flash Rate	1Hz (Switchable to 0.5Hz)
Operating Temperatures	-25°C to +70°C
Monitoring	Reverse Polarity
Protection	IP33C Shallow Base IP65 Deep and U Base
Weight	100g
Body Colour	White or Red
Flash Colour	White or Red
Approvals	Conforms to AS7240.23 EN54.23

*CNPP test results

Dimensions

