

Brooks Strobe

BS10601	Strobe 10-60VDC Blue Shallow
BS10602	Strobe 10-60VDC Amber Shallow
BS10603	Strobe 10-60VDC Red Shallow
BS10604	Strobe 10-60VDC Green Shallow
BS10605	Strobe 10-60VDC Clear Shallow



The Brooks range of xenon strobes provide a wide DC operating voltage, increased efficiency and automatic synchronisation making them a universal solution for all types of alarm and monitoring systems.

Features

- Wide operating voltage up to 60Vdc
- Current surge suppression
- Automatic synchronisation
- High efficiency
- Constant performance over voltage range
- Locking base
- Tamper switch for security applications
- Five lens colours

Technical Specification

Voltage	10 to 60VDC or 230V
Current	Solex 10 – 80mA @ 24VDC
Light source	Xenon
Light output	Solex 10 – 10Cd
Flash rate	1Hz
Synchronisation	10ms over 30mins
Temperature	-25°C to +70°C
Monitoring	Reverse polarity
Anti-tamper (where fitted)	Normally closed contact. Contacts open when beacon removed from base
Protection	IP54 shallow base IP65 deep
Construction	Base ABS FR Lens PC
Weight	0.15kg – Shallow base 0.18kg – Deep & U base
Lens colour	Red, amber, blue, green, or clear

Compatible Devices

BR240V	Mains Base Red
BW240V	Mains Base White
MROB0719R	Deep Base Red
MROB0719	Deep Base White