

EiB3028 - Heat & Carbon Monoxide Alarm

**Mains Powered 230V ~
Rechargeable Battery Backup**

Key Features

- Contains a Heat and CO sensor with 10 year life
- SmartLINK compatible
- AudioLINK+ data download
- Hardwire interconnect
- Optional wireless interconnect (with EiB3000MRF module)

Product Description

The EiB3028 is a dual Heat and Carbon Monoxide (CO) Alarm. It contains a proven electrochemical CO sensor to detect the presence of toxic levels of Carbon Monoxide as well as an independent fast acting Class A1 Thermistor sensor to detect dangerous levels of heat, hence eliminating the need for installing 2 products in areas where both types of detection would be required.

The EiB3028 is powered by 230V AC mains. In the event of mains failure, the rechargeable 10 year built in tamper-proof Lithium cells will provide up to 3 months power supply in the case of a wireless RF installation or up to 6 months in any other case.

The AudioLINK feature facilitates acoustic download of the Alarm parameters and status using the Ei Electronics AudioLINK app.

The EiB3028 can be interconnected via hardwire or wirelessly (through the EiB3000MRF module) enabling it to communicate with compatible Brooks Alarms and accessories. Up to 12 devices can be interconnected.

During an alarm, 'Fire' or 'CO' will flash on the Alarm to indicate what has been detected. The flash rate of the red LED is dependent on the type of detection and in case of CO, on the level detected.

The EiB3028 self-checks its sensors, battery voltage and internal circuitry every 48 seconds. Any fault condition found will be indicated by a combination of yellow LED flashes and chirps.

The memory feature allows an Alarm that has previously activated to be easily identified (through the red flashing LED).

Compatibility

Hardwire: BA128, EiB128RBU, EiB140e Series, EiB160e Series, EiB428RF, EiB3000 Series, FAC20, and Visalert.

Wireless: SmartLINK EiB3000MRF, EiB168RC, EiB170RFAU, EiB407RF, EiB408RF, EiB408RFH, EiB413, EiB428RF, EiB450, and any Alarm fitted with the RF module.

Product Replacement

Direct Replacement For: N/A



Technical Specifications

Sensor Type:	Thermistor (trigger temperature 58°C ± 4°C)
Product Life:	10 Years
Supply Voltage:	230V AC, 50Hz
Power Consumption:	0.25W (standby)
Battery Backup:	Tamper-proof rechargeable Lithium cells
Interconnectable:	Via hardwire (wireless optional with EiB3000MRF)
Sound Level:	85 dB(A) at 3m
Button Test:	Checks sensor, electronics and horn
Silence Function:	Silences alarm for 10 minutes Silences fault chirps for 12 hours
Live Monitoring:	Via the EiB3000MRF module and the EiB1000G Gateway
Data Download:	Via the AudioLINK App
Visual Indicators:	Green LED: Power Red LED: In alarm (if coincides with horn sounding), in hush mode or memory Yellow LED: Fault
Memory Feature:	Records last alarm event
End of Life:	Audible and visual indicators (3 yellow flashes and 3 beeps)
Temperature Range:	-10°C to 40°C ¹
Humidity Range:	15% to 95% Relative Humidity (non-condensing) ¹
Plastic Material:	UL94V0 flame retardant
Fixing:	Screw fixings and Easi-fit base supplied
Dimensions:	Product: 150mm x 66mm Packaging: 180mm x 155mm x 72mm
Weight:	312g (Pack + 66g)
Warranty:	5 year (limited) warranty
Approvals:	AS1603.3:2018



KM 86596
EN50291-1:2018

Manufactured to ISO 9001 quality standards
Specifications are subject to change

¹ Temperature and Humidity conditions are for normal operation and storage. Units will function outside these ranges as required by the specific product Standards. Extended exposure to conditions outside these ranges can reduce product life. For advice on prolonged operation outside these ranges consult the manufacturer.