

EiB3014 - Heat Alarm

**Mains Powered 230V ~
Rechargeable Battery Backup**

Key Features

- Fast acting Thermistor for Class A1 Heat detection
- SmartLINK compatible
- AudioLINK+ data download
- Hardwire interconnect
- Optional wireless interconnect (with EiB3000MRF module)

Product Description

The EiB3014 is a Heat Alarm with a Class A1 heat detection. It is ideal for rooms where smoke Alarms cannot be installed without the risk of excessive nuisance alarms like the kitchen, garage, etc.

The EiB3014 can only be used as part of a fire detection system ie: interconnected with Brooks mains powered Multi-Sensor or Smoke Alarms. It can be interconnected either by hardwire or wirelessly (using the EiB3000MRF module). Up to 12 devices can be interconnected.

The AudioLINK feature facilitates acoustic download of the Alarm parameters and status using the Ei Electronics AudioLINK app.

The EiB3014 is powered by 230V AC mains. In the event of mains failure, the rechargeable 10 year built in tamper-proof Lithium cells will provide up to 3 months power supply in the case of a wireless RF installation or up to 6 months in any other case.

The EiB3014 self-checks its sensor, battery voltage and internal circuitry every 48 seconds. Any fault condition found will be indicated by a combination of yellow LED flashes and chirps.

The memory feature allows an Alarm that has previously activated to be easily identified (through the red flashing LED).

Compatibility

Hardwire: BA128, EiB128RBU, EiB140e Series, EiB160e Series, EiB428RF, EiB3000 Series, FAC20, and Visalert.

Wireless: SmartLINK EiB3000MRF, EiB168RC, EiB170RFAU, EiB407RF, EiB408RF, EiB408RFH, EiB413, EiB428RF, EiB450, and any Alarm fitted with the RF module.

Product Replacement

Direct Replacement For: N/A



Technical Specifications

Sensor Type:	Thermistor (trigger temperature 58°C ± 4°C)
Product Life:	10 Years
Supply Voltage:	230V AC, 50Hz
Power Consumption:	0.25W (standby)
Battery Backup:	Tamper-proof rechargeable Lithium cells
Interconnectable:	Via hardwire (wireless optional with EiB3000MRF)
Sound Level:	85 dB(A) at 3m
Button Test:	Checks sensor, electronics and horn
Silence Function:	Silences alarm for 10 minutes Silences fault chirps for 12 hours
Live Monitoring:	Via the EiB3000MRF module and the EiB1000G Gateway
Data Download:	Via the AudioLINK App
Visual Indicators:	Green LED: Power Red LED: In alarm (if coincides with horn sounding), in hush mode or memory Yellow LED: Fault
Memory Feature:	Records last alarm event
End of Life:	Audible and visual indicators (3 yellow flashes and 3 beeps)
Temperature Range:	-10°C to 40°C ¹
Humidity Range:	15% to 95% Relative Humidity (non-condensing) ¹
Plastic Material:	UL94VO flame retardant
Fixing:	Screw fixings and Easi-fit base supplied
Dimensions:	Product: 150mm x 66mm Packaging: 180mm x 155mm x 72mm
Weight:	312g (Pack + 66g)
Warranty:	5 year (limited) warranty
Approvals:	AS1603.3:2018



Manufactured to ISO 9001 quality standards
Specifications are subject to change

¹ Temperature and Humidity conditions are for normal operation and storage. Units will function outside these ranges as required by the specific product Standards. Extended exposure to conditions outside these ranges can reduce product life. For advice on prolonged operation outside these ranges consult the manufacturer.