

4620AU Addressable Base Station for Wireless Devices



The 4620AU Addressable Base Station interfaces wireless devices to a COM loop in FT1020G3 or FT128. Up to 4 base stations can be monitored on each COM loop and up to 16 Wireless photoelectric smoke detectors on each base station. The base station comes with a built-in short circuit COM loop isolator.

Features

- Built-in short circuit isolator, requires no separate loop address
- 2 x built-in antennas

Technical Specification

Voltage	24V DC 40mA
Operating Temperature	-10 to +55°C
Ambient Humidity (%)	Max. 95%, non-condensing
Frequency	916MHZ
Transmission Range	Minimum 170m in open air
Dimensions (mm)	240 x 150 x 31
Weight	~345g

Conformance

AS7240.17-2015, AS7240.18-2015, AS 7240-25:2010 & AS/NZS4268:2017



Compatibility

FT128V2	Single Loop FireTracker Analogue Addressable Fire Indicator Panels ≥ EBL V2.4.X
FT1202G3	4 Loop FireTracker Analogue Addressable Fire Indicator Panels ≥ EBL V2.4.X

Compatible Devices

4611AU	Wireless Photoelectric Smoke Detector with inbuilt Sounder
4613AU	Wireless Signal Sniffer